



Protecting Indoor Air and Surfaces™



Features ActivePure Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The Aerus® AP500 is our smallest-profile product Powered by ActivePure® Technology, mounting directly into a standard wall outlet. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica


THE BENEFITS

The AP500 utilizes our proprietary ActivePure Technology to effectively treat indoor air and exposed surfaces, helping to reduce surface and airborne contaminants, allergens, and odors. A powerful, inconspicuous air purification system intended for use in small spaces.

- Disinfects surfaces and air, removes VOC gases, smoke and odor
- Compact, natural air treatment system for up to 250 sq. ft.
- Plugs into standard 120 volt electrical outlet
- Anti-theft mounting arrangement, no wiring required



¹View test results at Aerusonline.com/Scientific-Proof



Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation

Assembled in USA



SPECIFICATIONS

Product Information 00693 Model: A1028A
This unit does not meet California requirements and can not be shipped in California.

Technology Included ActivePure® Technology

Electrical Supply Voltage: 120V~, 60 Hz, .18 Amp,
Power Consumption: 13 Watts

Mechanical One control switch, on/off

Weight & Dimensions 2.9 lbs (1.3 kg)
12"H x 6"W x 4"D
(30 cm H x 15.24 cm W x 10 cm D)

Coverage¹ Up to 250 sq. ft. (23 m²) depending on occupant density and other factors¹.
High density commercial not to exceed 100 sq. ft. (9 m²).

Warranty Limited 3 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection.