



Air You Can Trust™

Features ActivePure Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold¹

THE TECHNOLOGY

The Aerus® Pure Cloud provides ActivePure Technology in the form of a 2' x 2' ceiling tile for situations when a portable unit cannot fit in the room. Patented ActivePure Technology is an advanced air and surface purification technology. It has been proven to reduce up to 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce numerous contaminants and pathogens, including the following¹:

- *Aspergillus niger* endospores
- *Aspergillus versicolor*
- *Bacillus globigii*
- *Botrytis cinerea*
- *Candida auris*
- *Clostridium difficile*
- *E. coli*
- *Erwinia herbicola*
- H1N1 Influenza
- H5N8 Influenza
- *Legionella pneumophila*
- *Listeria monocytogenes*
- Monkeypox virus (MPXV)
- MRSA
- MS2 Bacteriophage
- Murine Norovirus
- *Mycobacterium tuberculosis* (TB)
- PhiX-174
- Respiratory syncytial virus (RSV)
- SARS-CoV-2
- *Salmonella enterica*
- *Sclerotinia sclerotiorum*
- *Staphylococcus aureus*
- *Staphylococcus epidermidis*

THE BENEFITS

The Aerus Pure Cloud provides 24/7 air purification and surface decontamination in indoor spaces up to 2,500 sq. ft., while the unit is running. It is a proactive and effective solution for your home or business.

- Uses ActivePure Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold in indoor air and surfaces¹
- Reduces VOC gases, smoke, and odors without the use of ozone¹
- Discreet and easy installation
- Whisper-silent operation



Inducted into the 2017 Space Technology Hall of Fame by the Space Foundation



¹ View test results at Aerisonline.com/Scientific-Proof



PURE CLOUD



Product Information	00672 (120V) Model: A1021C 9960026 (230V) Model: A1021B
Environmental Certifications	Model A1021C Meets California ozone emissions limit. CARB Certified. Model A1021C validated to UL 2998
Technology Included	ActivePure® Technology - (1) 14" Cell Assembly
Electrical	110-120V 60Hz .75A (90W) / 220V - 240V 50Hz 0.3 Amp
Mechanical	100 CFM (Fan) 2.83 m³/min, impedance protected motor UV-C bulb, 26 watts, safety power switch
Safety	Conforms to UL 507
Weight & Dimensions	12 lbs (5.44 kg) 24" H x 24" W x 5" D (60.96 cm H x 60.96 cm W x 12.7 cm D)
Operating Temperature	34°F - 200°F (1.1°C - 93°C)
Coverage	Residential not to exceed 2,500 sq. ft. (232 m²). High Density Commercial not to exceed 1,000 sq. ft. (92 m²). ¹
Warranty	Limited 3 year warranty

1. Recommended ceiling height to not exceed 10 ft. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable occupant density, known VOC concentrations, and other layers of protection.



Contact Name: _____



Email: _____



Phone Number: _____