



AERUS

Protecting Indoor Air and Surfaces™



Features ActivePure® Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The Sanctuary Mini EM allows you to retrofit your mini-split HVAC system with ActivePure Technology. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Sanctuary Mini EM provides surface decontamination and air purification without the use of ozone. It is a proactive and effective solution for your home or business.

- Over a decade of testing, patented ActivePure® Technology has been proven to reduce over 99.9% of many common airborne and surface contaminants including viruses, bacteria, mold, fungi, VOC gases, smoke, allergens, and odors (full list of tested pathogens available in “The Proof” section)
- Provides 24/7 surface decontamination & air purification when the HVAC system is running
- Discreet or concealed installation, attaches easily to mini-split HVAC systems
- Requires only 20 watts of electricity



¹View test results at
Aeronline.com/Scientific-Proof



Inducted into the
2017 Space Technology
Hall of Fame by
the Space Foundation

Assembled in USA

SANCTUARY MINI EM

SPECIFICATIONS

Product Information	00670 Model: A1020B This unit does not meet California requirements and cannot be shipped to California.
Technology Included	ActivePure® Technology
Electrical	Input Voltage: 230VAC; 60Hz Current: 0.2A @ 120VAC Power Factor: 0.99 Power: 20W Max
Mechanical	Air Exchange: Distribution via air handler
Weight & Dimensions	1.0 lb (0.45 kg) 29.75" L x 2.63" W x 1.25" H (75.57 cm L x 6.67 cm W x 3.18 cm H)
Operating Temperature	35°F - 131°F (1.6°C - 55°C)
Coverage¹	Up to 500 sq. ft. (46.4 m ²) depending on occupant density and other factors ¹ .
Warranty	Limited 5 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection